

Betongroterare

Truck-Mixers | Fahrmischer



Tekniska fakta • Technical Data • Technische Daten

Roterare / Truck-Mixer / Fahrmischer		LT40 H	LT40 D	LT50 H	LT50 D	LT60 H	LT60 D	LT70 H	LT70 D	LT80 H	LT80 D	LT90 HI	LT90 DI	LT100 HI	LT100 DI	LT130 HI	LT130 DI
Kapacitet Nominal capacity Nennfüllung	litres	4000	4000	5000	5000	6000	6000	7000	7000	8000	8000	9000	9000	10000	10000	12000	12000
Volym Geometrical volume Ges. Volumen	litres	8322	8322	9440	9440	10592	10592	12766	12766	13800	13800	13729	13729	16500	16500	18500	18500
Fyllningsgrad Filling ratio Füllungsgrad	%	49	49	49	49	58	58	58	58	58	58	58	58	61	61	65	65
Effekt Required power Leistungsbedarf	kw	35	35	40	40	46	46	52	52	58	58	70	70	77	77	77	77
Roterarhastighet Drum speed Drezahl der Trommel	1/min	0÷14	0÷14	0÷14	0÷14	0÷14	0÷14	0÷14	0÷14	0÷14	0÷14	0÷14	0÷14	0÷14	0÷14	0÷14	0÷14
Vatten meter Water meter Wasseruhr	m³/h	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
Vattentank Water tank Wassertank	litres	400	400	400	400	650	650	650	650	650	650	1000	1000	1000	1000	1000	1000
A min. längd A min. length A. L min	mm	4760	5040	4975	5260	5335	5620	5820	6100	6045	6490	6490	6490	6300	6470	7730	7730
F min. bredd F min. width Fahrzeug-Verladerbreite	mm	2300	2300	2300	2300	2300	2300	2300	2300	2300	2300	2350	2350	2350	2350	2350	2350
H höjd H height Höhe Aufbau	mm	2380	2380	2436	2436	2535	2535	2665	2665	2672	2672	2672	2672	2717	2717	2800	2800
Tomvikt Empty weight Gewicht	kg	2800	3250	2900	3350	2950	3500	3350	4000	3900	4350	4100	4700	4300	4900	5150	5850

H: P.T.O/Kraftuttag
D: Hjälpmotor / Aux. engine / Hilfsmotor

Vikt tolerans enligt DIN 70020
Weights according DIN 70020
Gewichtstoleransen nach DIN 70020

Alla tekniska uppgifter kan ändras utan förbehåll
All data subject to change without prior notice
Sämtliche technische Angaben können ohne Voranzeige geändert werden



LT40 - LT50



LT50 - LT60



LT70 - LT80 - LT90 I - LT100 I



LT80 - LT90 I - LT100 I



LT130 I